

# PENETRATE HD Low VOC

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 08/04/2014

Revision date: 08/04/2014

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : PENETRATE HD Low VOC (25%) 12 & 17oz – Meets 2014 CA CARB standards  
Product code : 61107 & 61108 (1000024359 & 1000024380)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Penetrating Lubricant

#### 1.3. Details of the supplier of the safety data sheet

ClenAir Mfg., Inc.  
Box 346  
Fort Washington, PA 19034  
T- 888 764-2110

#### 1.4. Emergency telephone number

Emergency number : Chemtrec –(800) 424-9300 (24Hr)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flammable Aerosol 2  
Gases Under Pressure -Compressed gas  
Acute toxicity 4 (Inhalation)  
Skin irritation 2  
Eye irritation 2A  
Skin sensitization 1  
Germ cell mutagenicity 1B  
Carcinogenicity 1B  
Specific target organ toxicity - Repeated exposure 2

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause cancer. May cause genetic defects. May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS-US) :

Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe gas/mist/vapors/spray. If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

#### 2.3. Other hazards

No additional information available

# PENETRATE HD Low VOC

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### 2.4. Unknown acute toxicity (GHS-US)

20 percent of the mixture consists of ingredient(s) of unknown acute toxicity.

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Distillates, petroleum, hydrotreated heavy naphthenic	(CAS No) 64742-52-5	30 - 60	Carc. 1B
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	10 - 30	Flam. Liq. 3 Skin Irrit. 2 Eye Irrit. 2A Muta. 1B Carc. 1B
Pine, extract	(CAS No) 94266-48-5	7 - 13	Skin Irrit. 2 Eye Irrit. 2A Skin Sens. 1
Distillates, petroleum, hydrotreated middle	(CAS No) 64742-46-7	3 - 7	Flam. Liq. 4 Acute Tox. 4 (Inhalation) Skin Irrit. 2 STOT RE 2
Distillates, petroleum, hydrotreated heavy paraffinic	(CAS No) 64742-54-7	3 - 7	Acute Tox. 4 (Inhalation) Carc. 1B
Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based, containing solvent deasphalted residual oil	(CAS No) 72623-84-8	3 - 7	Carc. 1B
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based, high-viscosity	(CAS No) 72623-85-9	3 - 7	Acute Tox. 4 (Inhalation) Carc. 1B
Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based	(CAS No) 72623-86-0	3 - 7	Carc. 1B
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based	(CAS No) 72623-87-1	3 - 7	Acute Tox. 4 (Inhalation) Carc. 1B
2-Butoxyethanol	(CAS No) 111-76-2	1 - 5	Flam. Liq. 3 Acute Tox. 4 (Inhalation) Acute Tox. 4 (Oral, Dermal) Skin Irrit. 2 Eye Irrit. 2A
2-Butanol	(CAS No) 78-92-2	1 - 5	Flam. Liq. 3 Eye Irrit. 2A STOT SE 3
Carbon dioxide	(CAS No) 124-38-9	1 - 5	Compressed gas

\* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation	: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
First-aid measures after ingestion	: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Harmful if inhaled. May cause respiratory tract irritation. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause sensitisation by skin contact.
Symptoms/injuries after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/injuries after ingestion	: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

# PENETRATE HD Low VOC

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Treat for surrounding material.  
Unsuitable extinguishing media : None known.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.  
Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

#### 5.3. Advice for firefighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket.

#### 6.2. Methods and material for containment and cleaning up

For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).  
Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

#### 6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from sources of ignition. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/mist/vapours/spray. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.  
Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep locked up and out of reach of children. Do not expose to temperatures exceeding 50°C/ 122°F. Store away from direct sunlight or other heat sources. Store in a well-ventilated place.

#### 7.3. Specific end use(s)

Not available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.
Solvent naphtha, petroleum, light aromatic (64742-95-6)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.
Pine, extract (94266-48-5)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.
Distillates, petroleum, hydrotreated middle (64742-46-7)		
USA ACGIH	ACGIH TWA	Not applicable.

# PENETRATE HD Low VOC

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Distillates, petroleum, hydrotreated middle (64742-46-7)		
USA OSHA	OSHA PEL (TWA)	Not applicable.

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.

Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based, containing solvent deasphalted residual oil (72623-84-8)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.

Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based, high-viscosity (72623-85-9)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.

Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.

Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (72623-87-1)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.

2-Butoxyethanol (111-76-2)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	240 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm

2-Butanol (78-92-2)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	450 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	150 ppm

Carbon dioxide (124-38-9)		
USA ACGIH	ACGIH TWA (ppm)	5000 ppm
USA ACGIH	ACGIH STEL (ppm)	30000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	9000 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm

### 8.2. Exposure controls

Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Hand protection	: Wear chemically resistant protective gloves.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

# PENETRATE HD Low VOC

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid.
Appearance	: No data available.
Colour	: Red.
Odour	: Characteristic.
Odour threshold	: No data available.
pH	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: 171 - 254.4 °C (340 - 490 °F)
Flash point	: > 37.8 °C (> 100 °F)
Self ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Flammable.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: No data available.
Relative density	: 0.853
Solubility	: No data available.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: ~ 25 cSt @ 40 °C (104 °F)
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

#### 9.2. Other information

Flame projection length	: 0 cm
Heat of Combustion	: >30 kJ/g

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2. Chemical stability

Stable under normal storage conditions. Flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn.

#### 10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

#### 10.4. Conditions to avoid

Heat. Sources of ignition. Incompatible materials.

#### 10.5. Incompatible materials

Oxidizers.

#### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Harmful if inhaled.

PENETRATE HD 25% VOC 12OZ	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	>1.0 but ≤5.0 mg/l/4h

# PENETRATE HD Low VOC

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat	> 5.0 mg/l/4h

### Solvent naphtha, petroleum, light aromatic (64742-95-6)

LD50 oral rat	8400 ppm/4h
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h

### Distillates, petroleum, hydrotreated middle (64742-46-7)

LD50 oral rat	7400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	4.6 mg/l/4h

### Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

LD50 oral rat	> 15000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat	2.18 mg/l/4h

### Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based, high-viscosity (72623-85-9)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	2.18 mg/l/4h

### Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	2.18 mg/l/4h

### Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (72623-87-1)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	2.18 mg/l/4h

### 2-Butoxyethanol (111-76-2)

LD50 oral rat	470 mg/kg
LC50 inhalation rat	450 ppm/4h

### 2-Butanol (78-92-2)

LD50 oral rat	2193 mg/kg
LD50 dermal rat	> 2 g/kg
LC50 inhalation rat	16000 ppm/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

### 2-Butoxyethanol (111-76-2)

IARC group	3 - Not classifiable
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity

Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause respiratory tract irritation. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause sensitisation by skin contact.

# PENETRATE HD Low VOC

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

- Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Symptoms/injuries after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

### SECTION 12: Ecological information

#### 12.1. Toxicity

- Ecology - general : May cause long-term adverse effects in the aquatic environment.

#### 12.2. Persistence and degradability

##### PENETRATE HD 25% VOC 120Z

- |                               |                  |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |
|-------------------------------|------------------|

#### 12.3. Bioaccumulative potential

##### PENETRATE HD 25% VOC 120Z

- |                           |                  |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |
|---------------------------|------------------|

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

- Effect on ozone layer : No additional information available
- Effect on the global warming : No known ecological damage caused by this product.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.
- Additional information : Flammable vapours may accumulate in the container. Do not incinerate closed containers.

### SECTION 14: Transport information

In accordance with DOT

#### 14.1. UN number

- UN-No. : UN1950

#### 14.2. UN proper shipping name

- Proper Shipping Name : Aerosols flammable
- Department of Transportation Hazard Classes : 2.1
- Hazard labels :



#### 14.3. Additional information

- Other information : No supplementary information available.
- Special transport precautions : Do not handle until all safety precautions have been read and understood.

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

- |               |                   |
|---------------|-------------------|
| Pine, extract | CAS No 94266-48-5 |
|---------------|-------------------|

##### 2-Butanol (78-92-2)

Listed on SARA Section 313 (Specific toxic chemical listings)

- |                                       |       |
|---------------------------------------|-------|
| SARA Section 313 - Emission Reporting | 1.0 % |
|---------------------------------------|-------|

# PENETRATE HD Low VOC

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### 15.2. US State regulations


#### PENETRATE HD 25% VOC 12OZ

State or local regulations

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm. This product meets California 2014 CARB VOC standards for Penetrating lubricants (oils)

### SECTION 16: Other information

Indication of changes : None.  
Date of issue : 08/04/2014  
Other information : None.  
  
NFPA health hazard : 2  
NFPA fire hazard : 3  
NFPA reactivity : 0



*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*