

MARS HVAC/R Silicone Sealant is a superior quality silicone which remains flexible from -85° to 500°F. Never dries out. Has excellent adhesion to metals and can be used for virtually every HVAC need.

MARS RTV silicone sealants

MARS NO.	DESCRIPTION	MARS PACK	CASE QTY.
93246	silicone sealant almond	10.1 oz.	12
93249	silicone sealant clear	10.1 oz.	12
93251	silicone sealant white	10.1 oz.	12
93252	silicone sealant gray	10.1 oz.	12
93264	silicone sealant black	10.1 oz.	12
93253	silicone sealant clear	2.8 oz.	12
93254	silicone sealant white	2.8 oz.	12



MARS HVAC/R Hi-Temp Red Silicone Sealant is a superior quality silicone which was formulated to perform at temperatures ranging from -85°F to 500°F (-65°C to 260°C) for continuous operation and 600°F (316°C) for intermittent exposure. These features make MARS HVAC/R Hi-Temp red Silicone ideal for use around furnace vent pipes, restaurant hoods and heat exchangers.

MARS heat resistant silicone

MARS NO.	DESCRIPTION	MARS PACK	CASE QTY.
93255	Hi-Temp. silicone red	10.1 oz.	12
93247	heat resistant silicone red	2.8 oz.	12



Why every Professional Contractor should use Metacaulk 1000... Metacaulk 1000 is a water based, flexible, highly intumescent Firestop sealant designed for use on metal, insulated, fiberglass and plastic pipes. It can also be used for top of the wall construction joints, power and telephone cables. Metacaulk 1000 is specifically designed to fill voids in construction joints and around penetrations in fire rated walls or floors. Each time a fire rated wall or floor is penetrated, it must be restored to it's original fire rating. Metacaulk 1000 has intumescent properties which cause it to expand when heated, forming a high strength insulating char. In the event of fire, Metacaulk 1000 will restrict the spread of flames, smoke, hot gases and water through penetration openings and construction joints. Metacaulk 1000 has been tested in accordance with ASTM E814, UL 1479 and CAN4-S115M Fire Test Standards for up to a 4 hour fire rating in addition to ASTM E84, UL 723 Surface Burning Characteristics. It has also passed UL 2079 for top of the wall applications with fiberglass backing and as little as 1/4 inch depth of caulk. Metacaulk 1000 is non-sagging, non-toxic and has no VOC's. It will not emulsify after cure and is fully

Restorseal Metacaulk 1000 - Firestop Sealant

MARS NO.	DESCRIPTION	MARS PACK	CASE QTY.
93283	Firestop 10.3 oz.	24	24

