

SAFETY DATA SHEET

1. Product and Company Identification

Product identifier	Electrical Contact Cleaner - LV (4082-04)
Other means of identification	Not available
Recommended use	Cleaner
Recommended restrictions	None known.
Manufacturer	Nu-Calgon 2008 Altom Court St. Louis, MO 63146 US Phone: 314-469-7000 / 800-554-5499 Emergency Phone: 1-800-424-9300 (CHEMTREC)

2. Hazards Identification

Physical hazards	Gases under pressure	Liquefied gas
Health hazards	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Warning
Hazard statement	Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Suspected of damaging fertility or the unborn child. Contains gas under pressure; may explode if heated.

Precautionary statement

Prevention	Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist or vapor.
Response	If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see this label). If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned: Get medical advice/attention.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	67.22% of the mixture consists of component(s) of unknown acute oral toxicity.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Ethane, 1,1,1,2-tetrafluoro-		811-97-2	40 - 70
(E)-1,2-Dichloroethene		156-60-5	15 - 40
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-		138495-42-8	10 - 30
Ethanol		64-17-5	1 - 5
Methanol		67-56-1	0.1 - 1

Composition comments US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

4. First Aid Measures

Inhalation	If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
Skin contact	If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see product label).
Eye contact	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth.
Most important symptoms/effects, acute and delayed	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance. Do not puncture or incinerate container. Do not store at temperatures above 49°C.

5. Fire Fighting Measures

Suitable extinguishing media	Powder. Water spray. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. Cool containers with flooding quantities of water until well after fire is out. Firefighters should wear a self-contained breathing apparatus.
Special protective equipment and precautions for firefighters	Firefighters should wear full protective clothing including self contained breathing apparatus.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. Cool containers with flooding quantities of water until well after fire is out. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Cool containers exposed to flames with water until well after the fire is out.
Hazardous combustion products	May include and are not limited to: Oxides of carbon. Hydrogen chloride.
Explosion data	
Sensitivity to mechanical impact	Not available.
Sensitivity to static discharge	Not available.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid breathing gas. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Use personal protective equipment as required. When using, do not eat, drink or smoke. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material.

Conditions for safe storage, including any incompatibilities

Store locked up. Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Protect from sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
(E)-1,2-Dichloroethene (CAS 156-60-5)	PEL	790 mg/m3 200 ppm
Ethanol (CAS 64-17-5)	PEL	1900 mg/m3 1000 ppm
Methanol (CAS 67-56-1)	PEL	260 mg/m3 200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
(E)-1,2-Dichloroethene (CAS 156-60-5)	TWA	200 ppm
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
(E)-1,2-Dichloroethene (CAS 156-60-5)	TWA	790 mg/m3 200 ppm
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3 1000 ppm
Methanol (CAS 67-56-1)	STEL	325 mg/m3 250 ppm
	TWA	260 mg/m3 200 ppm

US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Ethane, 1,1,1,2-tetrafluoro- (CAS 811-97-2)	TWA	4240 mg/m3 1000 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Rubber gloves. Confirm with a reputable supplier first.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

Thermal hazards

Not applicable.

General hygiene considerations

Wash hands and face before breaks and immediately after handling the product. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not eat or drink.

9. Physical and Chemical Properties

Appearance	Clear
Physical state	Gas.
Form	Spray
Color	Water white
Odor	Ethereal
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	Not available.
Specific gravity	1.260
Partition coefficient (n-octanol/water)	Not available.
Flash point	Concentrate does not flash
Evaporation rate	> 1 (Water = 1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	50 - 60 psig @ 70°F
Vapor density	> 1 (Air = 1)
Relative density	Not available.
Solubility(ies)	Negligible
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	0.5 cP
Other information	
Flame projection	0 in
Heat of combustion	7.85 kJ/g

10. Stability and Reactivity

Reactivity	This product may react with strong oxidizing agents.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Do not mix with other chemicals. Aerosol containers are unstable at temperatures above 49°C (120.2°F).
Incompatible materials	Strong oxidizing agents. Caustics.
Hazardous decomposition products	May include and are not limited to: Hydrogen chloride. Oxides of carbon.

11. Toxicological Information

Routes of exposure	Inhalation. Ingestion. Skin contact. Eye contact.
Information on likely routes of exposure	
Ingestion	Harmful if swallowed.
Inhalation	Prolonged inhalation may be harmful. May cause irritation to the respiratory system.
Skin contact	Causes skin irritation. Contact with liquid may cause frostbite.
US ACGIH Threshold Limit Values: Skin designation	
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
US. NIOSH: Pocket Guide to Chemical Hazards	
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Eye contact	Causes serious eye irritation. Contact with liquid may cause frostbite.
Symptoms related to the physical, chemical and toxicological characteristics	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Harmful if swallowed. May cause respiratory irritation.

Components	Species	Test Results
(E)-1,2-Dichloroethene (CAS 156-60-5)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	5000 mg/kg
<i>Inhalation</i>		
LC50	Mouse	21723 ppm, 6 Hours
<i>Oral</i>		
LD50	Mouse	2220 mg/kg
	Rat	1235 mg/kg
Ethane, 1,1,1,2-tetrafluoro- (CAS 811-97-2)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 500000 ppm
<i>Oral</i>		
LD50	Not available	
Ethanol (CAS 64-17-5)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Mouse	39 mg/l, 4 Hours
	Rat	31623 ppm, 4 Hours
		20000 ppm, 10 Hours
<i>Oral</i>		
LD50	Dog	5500 mg/kg

Components	Species	Test Results
	Guinea pig	5600 mg/kg
	Mouse	3450 mg/kg
	Rat	7060 mg/kg
Methanol (CAS 67-56-1)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	15800 - 20000 mg/kg
	Rat	> 450000 mg/kg
<i>Inhalation</i>		
LC50	Cat	85.4 mg/l/4h
		43.7 mg/l, 6 Hours
	Rat	64000 ppm, 4 Hours
		87.5 mg/l, 6 Hours
		83.2 - 128.8 mg/l/4h
<i>Oral</i>		
LD50	Dog	8000 mg/kg
	Human	143 - 300 mg/kg
	Monkey	3000 mg/kg
		2000 mg/kg
	Mouse	7300 mg/kg
	Rabbit	14200 - 14400 mg/kg
	Rat	790 - 13000 mg/kg
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro- (CAS 138495-42-8)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg
<i>Inhalation</i>		
LC50	Rat	11100 ppm, 4 hours
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation. Contact with liquid may cause frostbite.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes serious eye irritation. Contact with liquid may cause frostbite.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Respiratory sensitization	Not available.	
Skin sensitization	Prolonged or repeated exposure can cause drying, defatting and dermatitis.	
US ACGIH Threshold Limit Values: Skin designation		
Methanol (CAS 67-56-1)	Can be absorbed through the skin.	
US. NIOSH: Pocket Guide to Chemical Hazards		
Methanol (CAS 67-56-1)	Can be absorbed through the skin.	
US ACGIH Threshold Limit Values: Skin designation		
Methanol (CAS 67-56-1)	Can be absorbed through the skin.	

US. NIOSH: Pocket Guide to Chemical Hazards

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

Germ cell mutagenicity	Non-hazardous by WHMIS/OSHA criteria.
Mutagenicity	Non-hazardous by WHMIS/OSHA criteria.
Carcinogenicity	Non-hazardous by WHMIS/OSHA criteria.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethanol (CAS 64-17-5)

Volume 44, Volume 96, Volume 100E
Volume 96, Volume 100E

Reproductive toxicity	Suspected of damaging fertility or the unborn child.
Teratogenicity	Methanol has produced teratogenic effects in mice exposed by inhalation to high concentrations that did not produce significant maternal toxicity.
Specific target organ toxicity - single exposure	Respiratory tract irritation.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not likely, due to the form of the product.
Chronic effects	Prolonged inhalation may be harmful.
Further information	Not available.
Name of Toxicologically Synergistic Products	Not available.

12. Ecological Information

Ecotoxicity	See below	
Components	Species	Test Results
(E)-1,2-Dichloroethene (CAS 156-60-5)		
Aquatic		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) 120 - 160 mg/l, 96 hours
Ethanol (CAS 64-17-5)		
Crustacea	EC50	Daphnia 11744.5 mg/L, 48 Hours
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 7.7 - 11.2 mg/l, 48 hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) > 100 mg/l, 96 hours
Methanol (CAS 67-56-1)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) > 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) > 100 mg/l, 96 hours
Persistence and degradability	No data is available on the degradability of this product.	
Bioaccumulative potential	No data available.	
Mobility in soil	No data available.	
Mobility in general	Not available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal Considerations

Disposal instructions	Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
US RCRA Hazardous Waste U List: Reference	
(E)-1,2-Dichloroethene (CAS 156-60-5)	U079
Methanol (CAS 67-56-1)	U154
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport Information

U.S. Department of Transportation (DOT)**Basic shipping requirements:**

UN number	UN1950
Proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Hazard class	Limited Quantity - US
Special provisions	N82
Packaging exceptions	306

Transportation of Dangerous Goods (TDG - Canada)**Basic shipping requirements:**


UN number	UN1950
Proper shipping name	AEROSOLS, flammable
Hazard class	Limited Quantity - Canada
Special provisions	80

IATA/ICAO (Air)**Basic shipping requirements:**

UN number	UN1950
Proper shipping name	Aerosols, flammable
Hazard class	Limited Quantity - IATA

IMDG (Marine Transport)**Basic shipping requirements:**

UN number	UN1950
Proper shipping name	AEROSOLS
Hazard class	Limited Quantity - IMDG

DOT; IMDG; TDG**IATA**

15. Regulatory Information

Canadian federal regulations

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Canada CEPA Schedule I: Listed substance

Ethane, 1,1,1,2-tetrafluoro- (CAS 811-97-2)	Listed.
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro- (CAS 138495-42-8)	Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Ethanol (CAS 64-17-5)	1 TONNES
Methanol (CAS 67-56-1)	1 TONNES

Canada SNAc Reporting Requirements: Listed substance/Publication date

Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro- (CAS 138495-42-8)	Listed. 11/29/2006
------------------------------------------------------------	--------------------

Food and Drug Administration (FDA)

Not regulated.

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Hazardous Substances (Director's): Listed substance

(E)-1,2-Dichloroethene (CAS 156-60-5) Listed.
 Ethanol (CAS 64-17-5) Listed.
 Methanol (CAS 67-56-1) Listed.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Methanol (CAS 67-56-1) Listed.

US - Illinois Chemical Safety Act: Listed substance

(E)-1,2-Dichloroethene (CAS 156-60-5) Listed.
 Ethanol (CAS 64-17-5) Listed.
 Methanol (CAS 67-56-1) Listed.

US - Louisiana Spill Reporting: Listed substance

(E)-1,2-Dichloroethene (CAS 156-60-5) Listed.
 Ethanol (CAS 64-17-5) Listed.
 Methanol (CAS 67-56-1) Listed.

US - Minnesota Haz Subs: Listed substance

(E)-1,2-Dichloroethene (CAS 156-60-5) Listed.
 Ethane, 1,1,1,2-tetrafluoro- (CAS 811-97-2) Listed.
 Ethanol (CAS 64-17-5) Listed.
 Methanol (CAS 67-56-1) Listed.

US - New Jersey RTK - Substances: Listed substance

(E)-1,2-Dichloroethene (CAS 156-60-5) Listed.
 Ethanol (CAS 64-17-5) Listed.
 Methanol (CAS 67-56-1) Listed.

US - New York Release Reporting: Hazardous Substances: Listed substance

(E)-1,2-Dichloroethene (CAS 156-60-5) Listed.
 Methanol (CAS 67-56-1) Listed.

US - Texas Effects Screening Levels: Listed substance

(E)-1,2-Dichloroethene (CAS 156-60-5) Listed.
 Ethane, 1,1,1,2-tetrafluoro- (CAS 811-97-2) Listed.
 Ethanol (CAS 64-17-5) Listed.
 Methanol (CAS 67-56-1) Listed.
 Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro- (CAS 138495-42-8) Listed.

US. Massachusetts RTK - Substance List

(E)-1,2-Dichloroethene (CAS 156-60-5) Listed.
 Ethanol (CAS 64-17-5) Listed.
 Methanol (CAS 67-56-1) Listed.

US. Pennsylvania RTK - Hazardous Substances

(E)-1,2-Dichloroethene (CAS 156-60-5) Listed.
 Ethanol (CAS 64-17-5) Listed.
 Methanol (CAS 67-56-1) Listed.

US. Rhode Island RTK

(E)-1,2-Dichloroethene (CAS 156-60-5) Listed.
 Methanol (CAS 67-56-1) Listed.

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	*	2
FLAMMABILITY		1
PHYSICAL HAZARD		0
PERSONAL PROTECTION		X



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

02-March-2015

Effective date

01-March-2015

Expiry date

01-March-2018

Further information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

Prepared by

Nu-Calgon Technical Service Phone: (314) 469-7000

Other information

This Safety Data Sheet was prepared to comply with the current OSHA Hazard Communication Standard (HCS) adoption of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

This SDS conforms to the ANSI Z400.1/Z129.1-2010 Standard.