

Inverter Driven Heat Pump

18,000 BTU Mid Static ducted

Job Name _____
 Location _____
 Engineer _____
 Submitted To _____
 Submitted By _____
 Reference _____

Date _____
 Approval _____
 Construction _____
 Unit No _____
 Drawing No _____

PRODUCT FEATURES

- Up to .80" WC
- Two wire or Three wire Controls
- Automatic Airflow Adjustment
- Heating operation rated down to -5°F outdoor temperature.
- Quiet Operation (as low as 24 decibels)
- Long Lineset Lengths (up to 164')



MODEL NUMBERS

Indoor Unit	ARU18RGLX
Outdoor Unit	AOU18RGLX
System	18RGLXD

EFFICIENCIES

SEER	19.0
EER	13.0
HSPF	10.9
COP	4.10
	14.0

OUTDOOR TEMPERATURE OPERATION RANGE

Cooling	*F(*C)	-5 to 115 (-20 to -46)
Heating		-5 to 75 (-20 to 24)

CAPACITIES

Cooling	Rated	BTU/hW	18,000
	Min.—Max.		5,400—21,500
Heating	Rated		21,000
	Min.—Max.		5,400—25,600

LINESET REQUIREMENTS

Connection Method	Flare
Liquid	Ø 1/4 (6.35)
Gas	Ø 1/2 (12.70)
Pre-Charge Length	65 (20)
Minimum Length	16 (5)
Maximum Length	164 (50)
Max. Height Diff.	98 (30)

INDOOR DIMENSIONS & WEIGHT

Net (H x W x D)	in	11-13/16 x 39-3/8 x 27-9/16
	mm	(300 x 1,000 x 700)
Gross (H x W x D)	in	15-3/4 x 48-3/4 x 34-7/16
	mm	(400 x 1,238 x 875)
Net Weight	lb (kg)	93 (42)
Gross Weight		110 (50)

OUTDOOR DIMENSIONS & WEIGHT

Net (H x W x D)	in	32-11/16 x 35-7/16 x 13
	mm	830 x 900 x 330
Gross (H x W x D)	in	39-3/8 x 41-5/16 x 17-1/2
	mm	1,000 x 1,050 x 445
Net Weight	lb (kg)	134 (61)
Gross Weight		152 (69)



Indoor Unit ETL#: 3170288
 Outdoor Unit ETL#: 91987

Effective Date: 11/20/2020

Fujitsu General America, Inc. • 370 Changebridge Road, Pine Brook, NJ 07058 • Toll Free: (888) 888-3424 • www.fujitsugeneral.com

Warranty Information



7 Year Compressor, 5 Year Parts out-of-the-box Warranty



10 Year Compressor, 10 Year Parts Warranty when registered within 30 days of installation in a residence



12 Year Compressor, 12 Year Parts Warranty when registered within 30 days of installation in a residence, and installed by a Fujitsu Elite contractor

ACCESSORIES

UTY-RNRUZ4	Wired Remote Control (Touch Screen)
UTY-RVNUM	Wired Remote Control
UTY-RSRY	Simple Remote Control
UTY-LBTUM	IR Receiver Kit
UTY-TTRX	Third Party Thermostat Adapter
UTY-TFSXZ2	WiFi Module
UTY-XSZX	Remote Sensor



This system combination is Energy Star qualified

Due to continuous product improvements, specifications are subject to change without notice. Please log in to the Fujitsu Portal for the most up-to-date documentation
<https://portal.fujitsugeneral.com>

Inverter Driven Heat Pump

18,000 BTU Mid Static ducted



FAN DATA				
Indoor Unit Airflow Rate	Cooling	High	CFM (m3/h)	618 (1050)
		Medium		494 (840)
		Low		430 (730)
		Quiet		371 (630)
	Heating	High		618 (1050)
		Medium		494 (840)
		Low		430 (730)
		Quiet		371 (630)
Outdoor Unit Airflow Rate	Cooling		1,177 (2,000)	
	Heating		1,489 (2,530)	
SOUND PRESSURE				
Indoor Unit	Cooling	High	dB (A)	31
		Medium		28
		Low		25
		Quiet		24
	Heating	High		31
		Medium		28
		Low		25
		Quiet		24
Outdoor Unit	Cooling		47	
	Heating		50	
REFRIGERANT				
Type				R410A
Charge	lb oz	4 lb 10.1oz		
	g	2,100		
Oil Type				POE (RB68)

ELECTRICAL SPECIFICATIONS					
Voltage/Frequency/Phase				208-230V/60Hz/1	
Voltage Range				187—253 V	
Current	Cooling	Rated	A	6.1	
	Heating	Rated		6.6	
Maximum Operating Current		Cooling		13.6	
		Heating		14.1	
Starting Current				6.6	
MCA				18.3	
Maximum Circuit Breaker				20	
Input Power	Cooling	Rated		kW	1.38
		Min.—Max.	0.53—2.08		
	Heating	Rated	1.5		
		Min.—Max.	0.51—2.19		
Power Factor	Cooling		%	98.4	
	Heating			98.8	
OTHER					
Moisture Removal		pints/h (L/h)		3.8 (1.8)	
Energy Star				YES	
Drain hose	Material	PVC			
	Size	in (mm) Ø 13/16 (20.7) [I.D.], Ø 1-1/16 (26.6)			
Operation Range	Cooling	°F (°C)	64 to 90 (18 to 32)		
		%RH	80 or less		
	Heating	°F (°C)	60 to 86 (16 to 30)		
Static Pressure Range		in. WG	0.12 - 0.80		
		Pa	30 - 200		

The Fujitsu logo is a worldwide trademark of Fujitsu General Limited. The Halcyon logo and name is a worldwide trademark of Fujitsu General Limited and is a registered trademark in Japan, the USA and other countries or areas. Copyright 2018 Fujitsu General America, Inc. Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.

Note: Specifications are based on the following conditions:
Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit – indoor unit).

DIMENSIONS



The Fujitsu logo is a worldwide trademark of Fujitsu General Limited. The Halcyon logo and name is a worldwide trademark of Fujitsu General Limited and is a registered trademark in Japan, the USA and other countries or areas. Copyright 2018 Fujitsu General America, Inc. Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.

Note: Specifications are based on the following conditions:
 Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit – indoor unit).