

Job Name	
Order No.	

# HITACHI

<b>Submittal Data Sheet</b>	RAK-DJ07QHAA
7,000 Btu/hr Wall Mounted Indoor Unit	



Indoor Specifications				
Airflow Rate (cfm)	Cooling		Heating	
	H	M	H	M
	260	180	310	210
	L	SL	L	SL
150	110	180	130	
Sound (dBA) H / M / SL			44/40/29	
Dimensions (W × H × D) (in) (mm)			30.71x11.02x8.74 (780x280x222)	
Weight (Lbs)			17.6	
Nominal Capacity (Btu/hr)			7,000	

Electrical		
	Cooling	Heating
Running Current (Rated) (A)	0.45	
Power Consumption (Rated) (W)	Refer to Outdoor	

Piping	
Liquid (in)	1/4
Gas (in)	3/8
Drain (in)	0.63

Recommended cable between Outdoor and Indoor 14AWG - 18AWG 4 conductors stranded copper wire and Power wiring cable size must comply with applicable national and local codes.

Optional Accessories:	
Description	Part Number
Remote Controller <b>(Included)</b> - N1	PMK-DJ09PHAAR05
Remote Control Support	PMK-DJ09PHAAR06
Remote Controller French - HN3	PMK-DJ09PHAAR95
Wired Controller	SPX-URFG1
16.4 ft (5m) wire cable for SPX-URFG1	SPX-WKT5M
Wi-Fi Adapter	SPX-WFA01
H-Link Adapter IDU	PSC-6RAD
Adapter for Wired Remote Group Controller	SPX-DST1
26.2 ft (8m) Wire Cable for Distributor SPX-DST1	SPX-WDST8M
Dry Contact	SPX-WDC3
ON/OFF Status and Alarm Signal	SPX-WDC8
Mini Aqua Univolt 100V – 250V	DPWM-83819
Condenser Stand	DL87743
Condenser Wall Bracket	DL87733
Test Switch Jig	PMRAC-X40G2 501

# Dimensional Data:

## Indoor Unit:

UNIT : Inch (mm)

