

Job Name	
Order No.	

HITACHI

Submittal Data Sheet	RAI-GJ24QHAA
24,000 Btu/hr Mini Cassette Indoor Unit	



Indoor Specifications				
Airflow Rate (cfm)	Cooling		Heating	
	H	M	H	M
	424	371	459	406
	L	SL	L	SL
318	229	353	265	
Sound (dBA) H / M / SL		Cooling		Heating
		43/39/29		44/40/30
Dimensions (H x W x D) (in)		11 x 22 x 22		
Weight (Lbs)		37		
Nominal Capacity (Btu/hr)		20500		

Electrical		
	Cooling	Heating
Running Current (Rated) (A)	0.25	
Power Consumption (Rated) (W)	Refer to Outdoor	

Piping	
Liquid (in)	1/4
Gas (in)	1/2
Drain (in)	1.26

Recommended cable between Outdoor and Indoor 14AWG - 18AWG 4 conductors stranded copper wire and Power wiring cable size must comply with applicable national and local codes.

Optional Accessories:	
Description	Part Number
Panel décor	P-AP56NAMRK
Float switch (Included)	E06200
Remote Controller with Receiver kit	SPX-RKCN2
Remote Controller French with Receiver kit	SPX-RKCN4
Wired Controller	SPX-URFG1
Wi-Fi Adapter	SPX-WFA01
H-Link Adapter IDU	PSC-6RAD
Extension Cable for Wifi Adapter	SPX-WFG58CM
Adapter for Wired Remote Group Controller	SPX-DST1
26.2 ft (8m) Wire Cable for Distributor SPX-DST1	SPX-WDST8M
Dry Contact	SPX-WDC3
ON/OFF Status and Alarm Signal	SPX-WDC8

Unit: inch(mm)

