

Job Name	
Order No.	

HITACHI

Submittal Data Sheet	RAF-FJ18QHAA
18,000 Btu/hr Floor Mounted Indoor Unit	



Indoor Specifications				
Airflow Rate (cfm)	Cooling		Heating	
	H	M	H	M
	416.7	321.4	434.5	339.3
	L	SL	L	SL
267.9	178.6	285.7	196.4	
Sound (dBA) H / M / SL		Cooling	Heating	
		43/36/23	44/36/26	
Dimensions (W × H × D) (in)		29.5 x 23.2 x 8.6		
Weight (Lbs)		32.4		
Nominal Capacity (Btu/hr)		18,000		

Electrical		
	Cooling	Heating
Running Current (Rated) (A)	0.4	
Power Consumption (Rated) (W)	Refer to Outdoor	

Piping	
Liquid (in)	1/4
Gas (in)	1/2
Drain (in)	0.63

Recommended cable between Outdoor and Indoor 14AWG - 18AWG 4 conductors stranded copper wire and Power wiring cable size must comply with applicable national and local codes.

Optional Accessories:	
Description	Part Number
Remote Controller (Included)	RAF-FJ07QHAA005
Remote Controller French	RAF-FJ07QHAA018
Wired Controller	SPX-URFG1
Wi-Fi Adapter	SPX-WFA01
H-Link Adapter IDU	PSC-6RAD
Adapter for Wired Remote Group Controller	SPX-DST1
26.2 ft (8m) Wire Cable for Distributor SPX-DST1	SPX-WDST8M
Dry Contact	SPX-WDC3
ON/OFF Status and Alarm Signal	SPX-WDC8

