

Genetron® 22

Version 2 Revision Date 10/01/2010 Print Date 11/15/2010

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Genetron® 22
MSDS Number : 000000009890
Product Use Description : Refrigerant

Company : Honeywell International, Inc.

101 Columbia Road

Morristown, NJ 07962-1057

For more information call : 800-522-8001

(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-651-523-0309

Transportation: 1-800-424-9300 or +1-703-527-3887

(24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : Liquefied gas

Color : colourless

Odor : slight

Hazard Summary : Warning! Container under pressure. This product is not

flammable at ambient temperatures and atmospheric pressure. Gas reduces oxygen available for breathing. Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating. Inhalation may cause

central nervous system effects. May cause cardiac arrhythmia. May cause drowsiness and dizziness. Do not breathe vapour. Irritating to eyes and skin. Avoid contact with skin, eyes and clothing. At higher temperatures, (>250°C), decomposition products may include hydrochloric acid (HCI), hydrofluoric acid (HF) and carbonyl halides. The ACGIH Threshold Limit Values (2007) for Hydrogen Fluoride are TLV-

TWA 0.5 ppm and Ceiling Exposure Limit 2 ppm.

Potential Health Effects

Skin : Avoid skin contact with leaking liquid (danger of frostbite).



Version 2 Revision Date 10/01/2010 Print Date 11/15/2010

May cause frostbite. Irritating to skin.

Eyes : Causes serious eye irritation.

May cause frostbite.

Ingestion : Unlikely route of exposure.

Effects due to ingestion may include:

Gastrointestinal discomfort

Inhalation : Gas reduces oxygen available for breathing.

Causes asphyxiation in high concentrations. The victim will

not realize that he/she is suffocating.

Inhalation may cause central nervous system effects.

May cause cardiac arrhythmia.

Vapours may cause drowsiness and dizziness.

Chronic Exposure : None known.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : CHCIF2

Chemical Name	CAS-No.	Concentration
Chlorodifluoromethane	75-45-6	100.00%

SECTION 4. FIRST AID MEASURES

Inhalation : Move to fresh air. If breathing is irregular or stopped,

administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do

not give drugs from adrenaline-ephedrine group.

Skin contact : After contact with skin, wash immediately with plenty of water.

If there is evidence of frostbite, bathe (do not rub) with

lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a

physician.



Genetron® 22

Version 2 Revision Date 10/01/2010 Print Date 11/15/2010

Eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.

Ingestion : Unlikely route of exposure. As this product is a gas, refer to the

inhalation section. Do not induce vomiting without medical

advice. Call a physician immediately.

Notes to physician

Treatment : Because of the possible disturbances of cardiac rhythm,

catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-

bitten areas as needed.

SECTION 5. FIRE-FIGHTING MEASURES

Flash point : not applicable

Lower explosion limit : None

Upper explosion limit : None

Suitable extinguishing

media

: The product is not flammable.

ASHRAE 34

Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Specific hazards during fire

fighting

: Contents under pressure.

This product is not flammable at ambient temperatures and

atmospheric pressure.

However, this material can ignite when mixed with air under

pressure and exposed to strong ignition sources.

Container may rupture on heating.

Cool closed containers exposed to fire with water spray.

Do not allow run-off from fire fighting to enter drains or water

courses.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing.

In case of fire hazardous decomposition products may be

produced such as:

Gaseous hydrogen chloride (HCI).



Version 2 Revision Date 10/01/2010 Print Date 11/15/2010

Hydrogen fluoride Carbon monoxide Carbon dioxide (CO2) Carbonyl halides

Special protective

equipment for fire-fighters

: In the event of fire and/or explosion do not breathe fumes.

Wear self-contained breathing apparatus and protective suit.

No unprotected exposed skin areas.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Immediately evacuate personnel to safe areas.

Keep people away from and upwind of spill/leak.

Wear personal protective equipment. Unprotected persons

must be kept away.

Remove all sources of ignition.

Avoid skin contact with leaking liquid (danger of frostbite).

Ventilate the area.

After release, disperses into the air.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing. Avoid accumulation of vapours in low areas.

Unprotected personnel should not return until air has been

tested and determined safe.

Ensure that the oxygen content is >= 19.5%.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

The product evaporates readily.

Methods for cleaning up : Ventilate the area.

SECTION 7. HANDLING AND STORAGE

Handling

Handling : Handle with care.

Avoid inhalation of vapour or mist.

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment.

Pressurized container. Protect from sunlight and do not expose

to temperatures exceeding 50 °C.

Follow all standard safety precautions for handling and use of

compressed gas cylinders.
Use authorized cylinders only.

Protect cylinders from physical damage.

Do not puncture or drop cylinders, expose them to open flame



Version 2 Revision Date 10/01/2010 Print Date 11/15/2010

or excessive heat.

Do not pierce or burn, even after use. Do not spray on a naked

flame or any incandescent material.

Do not remove screw cap until immediately ready for use.

Always replace cap after use.

Advice on protection against fire and explosion

: The product is not flammable.

Can form a combustible mixture with air at pressures above

atmospheric pressure.

Storage

Requirements for storage areas and containers

Pressurized container: Protect from sunlight and do not expose

to temperatures exceeding 50 °C. Do not pierce or burn, even

after use.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Storage rooms must be properly ventilated.

Ensure adequate ventilation, especially in confined areas.

Protect cylinders from physical damage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Do not breathe vapour.

Avoid contact with skin, eyes and clothing.

Ensure that eyewash stations and safety showers are close to

the workstation location.

Engineering measures : General room ventilation is adequate for storage and handling.

Perform filling operations only at stations with exhaust

ventilation facilities.

Eye protection : Wear as appropriate:

Safety glasses with side-shields If splashes are likely to occur, wear:

Goggles or face shield, giving complete protection to eyes

Hand protection : Leather gloves

In case of contact through splashing:

Protective gloves Neoprene gloves

Polyvinyl alcohol or nitrile- butyl-rubber gloves

Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).

Wear cold insulating gloves/face shield/eye protection.



Genetron® 22

Version 2 Revision Date 10/01/2010 Print Date 11/15/2010

Respiratory protection : In case of insufficient ventilation wear suitable respiratory

equipment.

Wear a positive-pressure supplied-air respirator.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing.

For rescue and maintenance work in storage tanks use self-

contained breathing apparatus.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Ensure adequate ventilation, especially in confined areas.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothing before re-use.

Keep working clothes separately.

Exposure Guidelines

Chlorodifluoromethane 75-45-6 ACGIH TWA 1,000 ppm

NIOSH STEL 1,250 ppm 4,375

mg/m3

NIOSH REL 1,000 ppm 3,500

mg/m3

OSHA Z1A TWA 1,000 ppm 3,500

mg/m3

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : Liquefied gas

Color : colourless

Odor : slight

Molecular Weight : 86.46 g/mol

pH : neutral

Melting point/range : -160 °C (-256 °F)

Boiling point/boiling range : -40.8 °C (-41.4 °F)

Vapor pressure : 9,384 hPa

at 21.1 °C (70.0 °F)

Page 6 / 11



Genetron® 22

Version 2 Revision Date 10/01/2010 Print Date 11/15/2010

Vapor pressure : 21,470 hPa

at 54.4 °C (129.9 °F)

Relative vapour density : 3

(Air = 1.0)

Density : 1.21 g/cm3

at 21.1 °C (70.0 °F)

Water solubility : 3.0 g/l

Partition coefficient: n-

octanol/water

: log Pow: 1.08 - 1.13

The product is more soluble in octanol.

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid : Pressurized container. Protect from sunlight and do not

expose to temperatures exceeding 50 °C. Decomposes under high temperature.

Some risk may be expected of corrosive and toxic

decomposition products.

Can form a combustible mixture with air at pressures above

atmospheric pressure.

Do not mix with oxygen or air above atmospheric pressure.

Materials to avoid : Finely divided aluminium

Potassium Calcium

Powdered metals

Aluminium Magnesium

Zinc

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be

produced such as:

Gaseous hydrogen chloride (HCI). Gaseous hydrogen fluoride (HF).

Carbonyl halides Carbon monoxide Carbon dioxide (CO2)

Thermal decomposition : >250 °C

Hazardous reactions : Hazardous polymerisation does not occur.

Stable under normal conditions.



Genetron® 22

Revision Date 10/01/2010 Print Date 11/15/2010 Version 2

SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity : LC50: > 300000 ppm

Exposure time: 4 h

Species: rat

Repeated dose toxicity : Species: rat

> Application Route: Inhalation Exposure time: Lifetime Exposure

NOEL: 10000 ppm

Note: Lifetime exposure of male rats was associated with a

small increase in salivary gland fibrosarcomas.

Further information : Acute toxicity Chlorodifluoromethane (HCFC-22): Cardiac

sensitisation threshold (dog): 50000 ppm. Rapid evaporation of the liquid may cause frostbite. Vapours are heavier than air and can cause suffocation by reducing oxygen available for

breathing. May cause cardiac arrhythmia.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Toxicity to fish : static test

LC50: 777 mg/l Exposure time: 96 h

Species: Danio rerio (zebra fish)

Toxicity to daphnia and other : static test

aquatic invertebrates.

EC50: 433 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea)

Further information on ecology

Additional ecological

information

: Accumulation in aquatic organisms is unlikely.

This product contains greenhouse gases which may

contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any



Version 2 Revision Date 10/01/2010 Print Date 11/15/2010

residual must be recovered.

This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.

Section 611 requires the following label text on all shipments

of this product:

Warning: Contains Chlorodifluoromethane (HCFC-22), a substance which harms public health and environment by

destroying ozone in the upper atmosphere.

Refer to sections 610 and 612 for list of acceptable and

unacceptable uses for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Information: Observe all Federal, State, and Local Environmental regulations.

Additional advice : This product is subject to U.S. Environmental Protection

Agency Clean Air Act Regulations Section 608 in 40 CFR Part

82 regarding refrigerant recycling.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 1018

Proper shipping name : CHLORODIFLUOROMETHANE

2.2

Class

Packing group

Hazard Labels 2.2

IATA UN/ID No. : UN 1018

Description of the goods : CHLORODIFLUOROMETHANE

Class : 2.2 Hazard Labels : 2.2 Packing instruction (cargo : 200

aircraft)

Packing instruction : 200

(passenger aircraft)

IMDG UN/ID No. : UN 1018

Description of the goods : CHLORODIFLUOROMETHANE

Class : 2.2
Hazard Labels : 2.2
EmS Number : F-C
Marine pollutant : no



Genetron® 22

Revision Date 10/01/2010 Print Date 11/15/2010 Version 2

SECTION 15. REGULATORY INFORMATION

Inventories

1907/2006 (EU) : This mixture contains only ingredients which have been subject

to a pre-registration according to Regulation (EC) No.

1907/2006 (REACH).

US. Toxic Substances

Control Act

: On TSCA Inventory

Australia. Industrial

Chemical (Notification and

Assessment) Act

: On the inventory, or in compliance with the inventory

Canada. Canadian **Environmental Protection** Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133) : All components of this product are on the Canadian DSL list.

Japan. Kashin-Hou Law

List

: On the inventory, or in compliance with the inventory

Korea, Toxic Chemical Control Law (TCCL) List : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control

Act

: On the inventory, or in compliance with the inventory

Chemical Substances

China. Inventory of Existing : On the inventory, or in compliance with the inventory

NZIOC - New Zealand : On the inventory, or in compliance with the inventory

National regulatory information

SARA 313 Components : Chlorodifluoromethane 75-45-6

SARA 311/312 Hazards : Acute Health Hazard

Sudden Release of Pressure Hazard



Genetron® 22

Revision Date 10/01/2010 Version 2 Print Date 11/15/2010

California Prop. 65 : This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

: Chlorodifluoromethane Massachusetts RTK 75-45-6

New Jersey RTK : Chlorodifluoromethane 75-45-6

Pennsylvania RTK : Chlorodifluoromethane 75-45-6

WHMIS Classification

This product has been classified according to the hazard criteria

of the CPR and the MSDS contains all of the information

required by the CPR.

Global warming potential : 1,500

Ozone depletion potential : 0.06

(ODP)

SECTION 16. OTHER INFORMATION

HMIS III **NFPA** Health hazard : 1 Flammability : 1 1

Physical Hazard : 0

Instability 0